















ELASTIC-Vollgummi-Räder



Serie 83 ST/5

Serie 73/5

 Artikelcode	 mm	 mm	 mm	 mm	 mm	 kg
73/100/040/5/15	100	40	45	45	15	160
73/125/040/5/15	125	40	45	45	15	180
73/125/050/5/20	125	50	54	60	20	225
73/125/050/5/25	125	50	54	60	25	225
73/160/050/5/20	160	50	54	60	20	300
73/160/050/5/25	160	50	54	60	25	300
73/180/050/5/20	180	50	54	60	20	350
73/180/050/5/25	180	50	54	60	25	350
73/200/050/5/20-1	200	50	54	54	20	400
73/200/050/5/20-2	200	50	54	60	20	400
73/200/050/5/25	200	50	54	60	25	400
73/250/050/5/20	250	50	54	60	20	500
73/250/050/5/25	250	50	54	60	25	500
73/300/060/5/30-1	300	60	60	60	30	650
73/300/060/5/30-2	300	60	75	74	30	650

 Artikelcode	 mm	 mm	 mm	 mm	 mm	 kg
83 ST/160/050/5/25	160	50	50	50	25	350
83 ST/200/050/5/25	200	50	50	50	25	400
83 ST/200/080/5/30	200	80	80	80	30	600
83 ST/250/050/5/25	250	50	50	50	25	400
83 ST/250/060/5/30	250	60	60	60	30	500
83 ST/250/080/5/30	250	80	80	80	30	700
83 ST/300/075/5/30	300	75	75	75	30	800

ELASTIC-Vollgummi-Räder

Aluminiumfelge mit fest aufvulkanisierter ELASTIC-Vollgummibereifung mit Rillenkugellagern (/5).

ELASTIC-Vollgummi-Räder

Hochstabile Stahlblechfelge, gepreßt, mit fest aufvulkanisierter ELASTIC-Vollgummibereifung mit Rillenkugellagern (/5).